

NEW DIGITAL PRESSURE MONITOR MD-DPC WITH SIGNAL OUTPUT

This completely redesigned digital pressure monitor for the display and monitoring of differential pressures in non-aggressive gases is the latest addition to our filter product portfolio.

So what exactly is new about it? More or less everything: a larger measuring range, a smaller measuring tolerance, improved overload protection, lower power consumption and a higher IEC protection class. Plus: a signal output, which is new. Not to forget the monitor's new compact size and hence lower weight.

If you order a pressure monitor now, you'll automatically get the new model. And you won't even have to pay more. If you want to use the pressure monitor for 230 V voltage, you'll need a power supply unit, which is available extra.

Here you see the differences at a glance:

Technical characteristics
Measuring range
Measuring tolerance
Overload protection
Medium
Supply voltage
Power consumption
Relay output
Signal output
Operating temperature
Display
Control
Casing
IEC protection class
Tube connection
Casing dimensions H x B x D
Weight

TROX South Africa (Pty) Ltd.



10 Wigford Road, Masons Mill
Pietermaritzburg 3201
Tel: +27 33 3981006

TROX South Africa - Sales Office

Unit 10 Corner Mini's
Horse Chestnut Avenue
Northlands Business Park
New Market Road
North Riding, Gauteng
Tel: +27 11 4626274

Online-Services

- > Order-Status (My TROX NET)
- > Your contact partner

Service-Hotlines

TROX South Africa (Pty) Ltd.
Tel: +27 33 3981006
Fax: +27 33 3981201

Postal Address:
P.O. Box 1250
Pietermaritzburg 3200
South Africa

E-Mail: info@troxsa.co.za

TROX IN SOCIAL WEB