



TYPE JN

Multi-leaf dampers are primarily used in ventilation systems for volume flow and pressure control. The blades are coupled by external linkage, which provide opposed blade operation. The damper has to be installed with horizontal blades. Casing and blades made from galvanised rolled sheet steel, casing flanges undrilled

- Blade spindles and external linkage made from galvanised steel,
- Plain bearings made from special plastic,
- Parallel blade operation, and opposed operation,
- Drive arm may be located on any blade,
- Temperature resistant to 100 °C,

Drive arm is made from galvanised steel. (An extended spindle can be supplied as an option for use by the client. However, this is standard when the damper is supplied with an electric.

TROX South Africa (Pty) Ltd.



10 Wigford Road, Masons Mill
Pietermaritzburg 3201
Tel: +27 33 3981006

TROX South Africa - Sales Office

Unit 10 Corner Mini's
Horse Chestnut Avenue
Northlands Business Park
New Market Road
North Riding, Gauteng
Tel: +27 11 4626274

Online-Services

- > [Order-Status \(My TROX NET\)](#)
 - > [Your contact partner](#)
-

Service-Hotlines

TROX South Africa (Pty) Ltd.
Tel: +27 33 3981006
Fax: +27 33 3981201

Postal Address:
P.O. Box 1250
Pietermaritzburg 3200
South Africa

E-Mail: info@troxsa.co.za

TROX IN SOCIAL WEB
